

[Find by Feature](#)
[Browse by Category](#)
[Share](#)
 [Search →](#)

Enter part number or keyword

[Search Results \(0\)](#)
[Search Options](#)

Select a product type to narrow your search:

Results with your selections: --

[Clear](#)
[Search →](#)

Female GT 280 Tin Plated Terminal, Cable Range 3.00 - 1.50 mm², Cable Insulation Range 3.20 - 2.20 mm

Part #15304720

Question about this product?

[Attributes](#)
[Documents \(13\)](#)

Part #:	15304720
Description:	Female GT 280 Tin Plated Terminal, Cable Range 3.00 - 1.50 mm ² , Cable Insulation Range 3.20 - 2.20 mm
Product Type:	Terminal
Status:	Active
Blade size [mm]:	2.8
Terminal family:	GT
Series:	280
Gender:	Female
Sealed:	Sealed
Material:	Tin Brass
Plating:	Tin
Minimum Cable Core Cross Section [mm²]:	1.50
Maximum Cable Core Cross Section [mm²]:	3.00
Minimum Cable Diameter [mm]:	2.20
Maximum Cable Diameter [mm]:	3.20

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.